

Indicative Round Stem Pull Tight Seal

Features

- The Fast Seal 3.5 is a strong and durable seal designed for longer seal length and stronger sealing requirements.
- The large flap area allows ample space for marking and barcoding.
- The embedded spikes at the back of the seal provide better strapping grip on bags or other slippery materials.
- A metal clip encapsulated by cap provides greater security and greater pull strength.
- The Fast Seal 3.5 is etched with secure and permanent laser marking for name, logo, sequential numbers & barcodes. Laser marking offers the highest level of security as it cannot be removed or replaced without tamper evidence.
- The options for durable Nylon or PP securing straps gives users different choices for strength customisation to match different applications.

Technical Specifications

PRODUCT - FAST SEAL 3.5

Product	Material	Locking Length	Strap Dimensions	Pull Strength	Marking Area	Max Marking Digits
RF3 300	Body: PP Coated & BioPlas Metal Plate: SS 304	300 mm (11.8 in)	ø 3.5 mm (0.0137 in)	>30 kg (PP) (>66.1 lbs)	Flap: 50 x 18 mm (1.97 x 0.71 in)	Serial no : 16 Barcode no: 16
RF3 450	Cap: PP	450 mm (17.7 in)	ø 3.5 mm (0.0137 in)	>35 kg (NY) (>77 1 lhs)	(=:=::::=:::,	

PACKAGING

	Quantity	Dimensions (mm)	Gross Weight kg	Volume m³	Standard Colours
Inner Carton RF3 300 RFS 450	1,000 1,000	568 x 235 x 180 22.36 x 9.252 x 7.086 (in) 615 x 280 x 280 24.21 x 11.02 x 11.02 (in)	6.2 13.67 lbs 7.7 16.98 lbs	0.024 (0.848 cu.ft.) 0.048 (1.695 cu.ft.)	PS.RED PS.BLUE PS.YELLOW PS.GREEN PS.ORANGE WHITE
Standard Pallet RF3 300 RFS 450	72,000 42,000	1200 x 1000 x 1770 47.24 x 39.37 x 69.69 (in) 1230 x 1000 x 2110 48.42 x 39.37 x 83.07 (in)	471.4 1039.3 lbs 348.8 768.97 lbs	2.124 (75.01 cu.ft.) 2.612 (92.24 cu.ft.)	

KEY APPLICATIONS

✓ Cash in Transit
 ✓ Retails Applications

✓ Logistics

✓ Tankers

✓ Mail and Courier















UPDATED: 19 SEPTEMBER 2019